

Geprüfte
Baustoffe aus
natürlichen und
nachwachsenden
Rohstoffen...

Das Hessler Kalksystem.

Hessler

KALK & PUTZ

Qualität seit 1881

Hessler Kalkwerke GmbH · 69154 Wiesloch · Postfach 1345 · Tel. 062 22/92 75-0



Mineralischer Putzgrundverfestiger

- Composition:** **Mineral Plaster Base Consolidator** consists of lithium oxide, silicon dioxide and water.
- Application range:** Lithium silicate is used to **consolidate** crumbling substrates such as mineral plaster and natural stone indoors and outdoors.
- Application:** Apply lithium silicate by paint brush, wide brush or spray gun. Lithium silicate penetrates into the surface and silicifies. This makes the substrate more resistant and solid for the subsequent plaster application. With **fresh** lime plaster, a drying time of **at least 8 weeks** must be observed before applying lithium silicate. Cover all surfaces not to be coated thoroughly.
- Consumption rate:** Dilute lithium silicate with water at a ratio of **1 : 1**.
Spreading rate: approx. 30 m² (depending on nature of substrate).
- Please note:** Do not use on gypsum or in case of bleeding substances. Substrates must be dry, absorbent, clean and free of bleeding substances. The air and/or object temperature must be **between 5 °C and 30 °C**.
- Container size:** 5 kg cans (approx. 5 litres)
- Storage:** Dry, shelf life at least 12 months in closed packaging
- Safety advice:** Wear protective gloves and eye protection during application. In case of contact, rinse thoroughly with water. Consult a doctor if symptoms persist. Immediately remove product splashes on surfaces not to be treated with plenty of water.

For more information, please contact us by phone or in writing at:
info@hessler-kalkwerk.de, or at: +49 6222/9275-0. We will be glad to assist you!

This information is based on our experience and does not take into account any specific case. No claims for damages can therefore be derived from it. All information without guarantee. Errors, typing errors and changes reserved.