

Geprüfte
Baustoffe aus
natürlichen und
nachwachsenden
Rohstoffen...

Hessler

KALK & PUTZ

Das Hessler Kalksystem.

Qualität seit 1881

Hessler Kalkwerke GmbH · 69154 Wiesloch · Postfach 1345 · Tel. 062 22/92 75-0



Punisches Wachs

Application range:

Punic Wax is used as a matt, or after polishing, as a glossy **surface coating** for smoothed Hessler natural lime finishing plaster (e.g. smoothing lime plaster, Marmorino, smoothed lime felt plaster, Tadelakt, etc.).

Application:

Apply Punic Wax with a **Venetian trowel**, plastic smoothing trowel or Japanese trowel. A second coat can be applied after approx. 1-4 hours (depending on temperature and humidity), if necessary. After flash-off, the wax can be **polished** with a soft cloth or a polishing machine. **Note:** The polishing machine may damage the surface if the speed or the pressure are too high.

Consumption rate:

Approx. 30 ml wax / m²

Please note:

The surface to be treated must be dry and free of dust. Allow the lime plaster to **stand for at least 2 weeks** before applying the wax. The air and/or object temperature must be **above 5 °C**. Clean tools and vessels with warm water.

Container size:

250 ml / 500 ml / 1,000 ml

Storage:

Punic wax must be stored in closed containers in a cool, dry place. Shelf life is at least 2 years if unopened, use opened containers within approx. 12 months.

Safety advice:

R 36 Irritating to eyes
R 41 Risk of serious damage to eyes

For more information, please contact us by phone or in writing at:
info@hessler-kalkwerk.de, or at: +49 6222/9275-0. We will be glad to assist you!

This information is based on our experience and does not take into account any specific case. No claims for damages can therefore be derived from it. All information without guarantee. Errors, typing errors and changes reserved.